




- NOTES:**
1. TOLERANCES PLUS OR MINUS 0.015 [0.38]
 2. CONTACT AREA SEALED TO IP67
 3. BACK OF SWITCH SEALED WHEN MATING CONNECTOR IS INSTALLED
 4. FOR RESISTIVE LOAD RATING SEE CHART OR BACK OF SWITCH
 5. KEY REMOVEABLE IN OFF POSITION ONLY
 6. FOR PIN LOCATIONS SEE CHART
 7. MATERIALS: HOUSING BLACK THERMOPLASTIC
INTERNAL STATIONARY CONTACTS COPPER
 8. START LOCKOUT FEATURE. SWITCH MUST GO TO "OFF" POSITION BEFORE THE START CIRCUIT CAN BE RE-ENERGIZED
 9. SWITCH TESTED TO SAE J259, UL RECOGNIZED TO UL 1054
 10. SW. MUST NOT BREAK CIRCUIT OR BE DAMAGED IF TORQUED TO 15 IN-LBS [1.69Nm]
 11. IF THE APPLICATION MOUNTS THE SWITCH WITH THE LOCK CYLINDER OR LEVER APPROACHING VERTICAL, CONTACT THE FACTORY FOR AN APPLICATION REVIEW AND POTENTIAL ALTERNATE PRODUCTS BEFORE DESIGN IS SET.

Revision Control Record				Revision Control Record				Tolerances				PROPRIETARY INFORMATION				Special Characteristics:				Cole Hersee Co.			
Rev.	Description of Change	ECN No.	Date	Rev.	Description of Change	ECN No.	Date	Unless otherwise specifically noted, the following are default tolerances:				This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.				Critical Characteristic, relating to Safety and/or Regulatory Compliance				20 Old Colony Ave., South Boston, MA, 02127			
				D	ADDED HEX NUT, 1.950	07102	3/30/07	* 2-place Decimal Dimensions +/- .02"				It is the responsibility of the individual using / referencing this drawing to assure that the noted design revision level agrees with the revision level of the Controlled Document (Master Drawing). This is a NON-CONTROLLED DOCUMENT unless otherwise specifically noted.				Significant Characteristic relating to Process Control (SPC)				Phn: 617-268-2100 Web: www.colehersee.com			
G	ADDED HENCOL 13; ADDED TORQUE NOTE	13169	6/17/13	C	REVISED NOTES; DELETED HEX NUT	07049	2/15/07	* 3-place Decimal Dimensions +/- .005"				DESIGN CONTROL				Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer				Description:			
F	ADDED MADE IN TAIWAN	11215	7/15/11	B	ADDED NOTES	06325	10/4/06	* Angular Dimensions +/- 1.0 Deg.				DO NOT SCALE - Dimensional variation may occur during printing / reproduction.				(Note that the identification of any Characteristics as being "Special" does not alter the requirement that ALL specified dimensions & tolerances must be met.)				SW, ROT, 4POS, PLSTC			
E	ADDED CHART & UL	10254	6/24/10	A	RELEASED DRAWING	06287	8/11/06	* Metric: Refer to equivalent English Dimension Tolerance				Used On or Ref.: EX28124				Responsible Engineer: JT				Drawing / Part No.:			
								>>> NOTE: All tolerances are Non-Cumulative. <<<				Scale: 1:1				PAGE 1				95060-11			
								Dimensional Units All dimensions are expressed in inches except those shown in brackets (xxx) are expressed in millimeters				Date Drawn: 8/11/06				Created using Autocad Inventor				Current Rev. G			