


4

3

2

1



METRIC

NOTES:

1. ALL STEEL PARTS PLATED
2. ALL DIMENSIONS REFERENCE ONLY
3. SILVER CONTACT SURFACES
4. RATING:

CONTINUOUS-175 AMPS, 6-12-24-36 VDC
INTERMITTENT-800 AMPS, 6-12-24-36 VDC
15 SECONDS ON, 5 MINUTES OFF, IGNITION PROTECTED

Revision Control Record				Rev.	Description of Change	ECN No.	Date	Tolerances Unless otherwise specifically noted, the following are default tolerances:			PROPRIETARY INFORMATION This Engineering Drawing, and the information contained herein, is proprietary to Cole Hersee Company and may not be disclosed, re-produced, or in any other way transferred or communicated to any other party without the express written consent of an authorized representative of Cole Hersee Company.		Special Characteristics:		Cole Hersee Co.		
Rev.	Description of Change	ECN No.	Date					2-places +/- 0.02"	3-places +/- 0.005"	Angular +/- 1°		☒ CC Critical Characteristic, relating to Safety and/or Regulatory Compliance	☒ Significant Characteristic relating to Process Control	☒ KC Control Dimension relating to Form - Fit - Function as defined by Cole Hersee Company and/or the Customer	20 Old Colony Ave., South Boston, MA, 02127 Phn: 617-268-2100 Web: www.colehersee.com		
H	UPDATED DRAWING FORMAT UPDATED LABEL	10016	01/13/10								Metric: Shown in [] refers to equivalent English Dim Tol				Description: SWITCH, MASTER DISCONNECT		
											"REF." or an Asterisk (*) = Non-Toleranced Reference Dimension, shown for clarification purposes only.						
											NOTE: All tolerances are Non-Cumulative.						
								FORM CHT-6 (2/07)	Used On or Ref.: 2484-A WITH UL LABEL			Scale: 1:1	Drawn BY: JAV	Date Drawn: 02/08/79	Pg. 1 of 1	Drawing / Part No.: 2484-16	
																Current Rev. H	

4

3

2

1