CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED (rev C)




NOTES:
1. MATERIAL: COPPER C1100, TIN PLATED
2. UNLESS OTHERWISE NOTED, BURR SHALL NOT EXCEED 10% OF THE RAW MATERIAL THICKNESS AT ANY LOCATION
3. PART TO BE CLEAN, DEGREASED, FREE OF CONTAMINATION

| NO | COMPONENT NO | DESCRIPTION | QTY/M | U/M |
|---|---|---|---|---|

BILL OF MATERIAL

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS.
DIMENSIONS IN BRACKETS [ ] ARE INCHES
UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

◎ DENOTES CRITICAL CHARACTERISTICS.
CPK DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
ST DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS
CP DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE

MATL SPEC: SEE NOTE
FINISH: SEE NOTE

| | | DATE | SCALE |
|---|---|---|---|
| DRW | FYUE | 06/26/13 | 1:1 |
| CHK | | DATE | SUPER DR |
| APPD | | DATE | FINSH GOOD WT GRAMS/PIECE |

COPIES TO: 1 9 18 / 2 10 19 / 3 12 20 / 4 13 21 / 5 14 23 / 6 15 33 / 7 16 43 / 8 17 53

TOLERANCES UNLESS OTHERWISE SPECIFIED (REF. ISO 2768-fH)

| | UP TO 3 | OVER 3 UP TO 6 | OVER 6 UP TO 30 | OVER 30 UP TO 120 | OVER 120 UP TO 400 |
|---|---|---|---|---|---|
| DIMENSION | 0.5 | ±0.05 | ±0.1 | ±0.15 | ±0.2 |
| TOLERANCE | ±0.05 | | | | |

3RD ANGLE PROJECTION

TITLE: 5 POSITION BUS BAR - FLEX MIDI HOLDER

Littelfuse® CHICAGO, USA 773-628-1000

REVISION: B
DRWG. NO. OL-882-267-005

| LTR | DATE | REVISION | CHK | APD |
|---|---|---|---|---|
| A | 06/26/13 | 508674ERA-RELEASE FYUE | | |
| B | 07/10/13 | 508881ECA-THICKNESS 2.3 WAS 2.0 FYUE | | |