

	REVISION			
REV DATE		DESCRIPTION		
Α	6/19/23	526604GCP - RELEASE MRY		

<s></s>	CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE					
•	DENOTES CRITICAL CHARACTERISTICS.					
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE					
<u>(ST)</u>	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.					
СР	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.					
MATL SPEC		FINISH				
JMoler	DATE 5/30/2023	SCALE NTS	FINISH GOOD WT GRAMS/PIECE			

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

3RD ANGLE PROJECTION

TITLE

KLC 225-400A OUTLINE



REVISION DRWG NO.

SHEET 1 OF 1

OL-0KLC400