		REVI	SION			
R	REV DATE DESCRIPTION					
	A 8/31/22	525	635GCP - RELEASE MRY	′		
85.1 [.945] [3.350]	1 NO COMPONE		SCRIPTION MATERIAL	QTY/M	U/M	
	<s></s>	CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE				
20.9	•	DENOTES CRITICAL CHARACTERISTICS.				
7.00 [.276] - 13.9 [.547] - 3.90 [.154]	СРК	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE				
	(ST)	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.				
	СР	ALLOW FOR MAXIMUM TOOL LIFE.				
	MATL SPEC		FINISH			
	DRW JMOLER	DATE 8/23/2022	SCALE NTS		MS/PIECE	
	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994					
	3RD ANGLE PROJECTION					
	CTPT5 OUTLINE REVISION DRWG NO. SHEET 1 OF 1 CHICAGO, ILLINOIS 60631 A OL-CTPT5					