

Prospective Data

Insulated Gate Bi-Polar Transistor

Type T0800TB45E

Absolute Maximum Ratings

	VOLTAGE RATINGS	MAXIMUM LIMITS	UNITS
V_{CES}	Collector – emitter voltage	4500	V
$V_{DC\ link}$	Permanent DC voltage for 100 FIT failure rate.	2800	V
V_{GES}	Peak gate – emitter voltage	± 20	V

	RATINGS	MAXIMUM LIMITS	UNITS
$I_{C(DC)}$	DC collector current, IGBT	800	A
I_{CRM}	Repetitive peak collector current, $t_p=1ms$, IGBT	1600	A
I_{ECO}	Maximum reverse emitter current, $t_p=100\mu s$, (note 2 & 3)	800	A
P_{MAX}	Maximum power dissipation, IGBT (Note 2)	6.4	KW
$(di/dt)_{cr}$	Critical diode di/dt (note 3)	1500	A/ μs
T_j	Operating temperature range.	-40 to +125	$^{\circ}C$
T_{stg}	Storage temperature range.	-40 to +125	$^{\circ}C$

Notes: -

- 1) Unless otherwise indicated $T_j = 125^{\circ}C$.
- 2) $T_{sink} = 25^{\circ}C$, double side cooled.
- 3) The use of an anti-parallel diode is recommended.

Characteristics

IGBT Characteristics

	PARAMETER	MIN	TYP	MAX	TEST CONDITIONS	UNITS
$V_{CE(sat)}$	Collector – emitter saturation voltage	-	2.8	3.2	$I_C = 800A, V_{GE} = 15V, T_J = 25^\circ C$	V
		-	3.5	3.9	$I_C = 800A, V_{GE} = 15V$	V
V_{T0}	Threshold voltage	-	-	1.71	Current range: 265 – 800A	V
r_T	Slope resistance	-	-	2.74		m Ω
$V_{GE(TH)}$	Gate threshold voltage	-	5.3	-	$V_{CE} = V_{GE}, I_C = 85mA$	V
I_{CES}	Collector – emitter cut-off current	-	10	35	$V_{CE} = V_{CES}, V_{GE} = 0V$	mA
I_{GES}	Gate leakage current	-	-	± 10	$V_{GE} = \pm 20V$	μA
C_{ies}	Input capacitance	-	135	-	$V_{CE} = 25V, V_{GE} = 0V, f = 1MHz$	nF
$t_{d(on)}$	Turn-on delay time	-	2	-	$I_C = 800A, V_{CE} = 2800V, di/dt = 1500A/\mu s$ $V_{GE} = \pm 15V, L_g = 200nH$ $R_{g(ON)} = 8.2\Omega, R_{g(OFF)} = 8.2\Omega, C_{GE} = 68nF$ Freewheel diode type E0900NC45C at $T_J = 125^\circ C$. (Notes 3, 4 & 5)	μs
$t_r(V)$	Rise time	-	4	-		μs
$Q_{g(on)}$	Turn-on gate charge	-	5	-		μC
E_{on}	Turn-on energy	-	7	-		J
$t_{d(off)}$	Turn-off delay time	-	4.5	-		μs
$t_f(I)$	Fall time	-	2.1	-		μs
$Q_{g(off)}$	Turn-off gate charge	-	9	-		μC
E_{off}	Turn-off energy	-	4.3	-		J
I_{SC}	Short circuit current	-	2500	-	$V_{GE} = \pm 15V, V_{CE} = 2800V, V_{CEmax} \leq V_{CES}, t_p \leq 10\mu s$	A

Thermal Characteristics

	PARAMETER	MIN	TYP	MAX	TEST CONDITIONS	UNITS
R_{thJK}	Thermal resistance junction to sink, IGBT	-	-	15.6	Double side cooled	K/kW
		-	-	25.6	Collector side cooled	K/kW
		-	-	40.6	Emitter side cooled	K/kW
F	Mounting force	15	-	25	Note 2	kN
W_t	Weight	-	1.2	-		kg

Notes:-

- 1) Unless otherwise indicated $T_J = 125^\circ C$.
- 2) Consult application note 2008AN01 for detailed mounting requirements
- 3) C_{GE} is additional gate – emitter capacitance added to output of gate drive
- 4) E_{on} integration time 15 μs from 10% rising I_C .
- 5) E_{off} integration time 15 μs from 90% falling V_{GE} .

Curves

Figure 1 – Typical collector-emitter saturation voltage characteristics




Figure 2 – Typical output characteristic




Figure 3 – Typical output characteristic




Figure 4 – Typical turn-on delay time vs gate resistance




Figure 5 – Typical turn-off delay time vs. gate resistance




Figure 6 – Typical turn-on energy vs. collector current




Figure 7 – Typical turn-on energy vs. di/dt




Figure 8 – Typical turn-off energy vs. collector current




Figure 9 – Turn-off energy vs voltage




Figure 10 – Safe operating area





Figure 11 – Transient thermal impedance



Technical drawing of the 171A108 vacuum tube, showing top and side views with dimensions and labels.

Top View Dimensions and Labels:

- $\phi 3.6/3.5 \times 2$ MIN DEPTH 2-HOLES, ONE IN EMITTER AND ONE IN COLLECTOR.
- GATE / EMITTER & MONITORING TERMINATIONS: STANDARD TABS 4.75×0.5 THICK
- GATE LIES BENEATH MONITORING TAB
- EMITTER
- 65 MAX (BOTH TABS)

Side View Dimensions and Labels:

- $\phi 112$ (Overall diameter)
- $\phi 75$ (Internal diameter)
- 0.8 MIN (Thickness of collector/emitter)
- COLLECTOR
- EMITTER
- MONITORING TAB
- 0.8 MIN (Thickness of monitoring tab)
- 4 TYP (Number of tabs)
- 26 ± 0.5 COMPRESSED HEIGHT
- $\phi 75$ (Internal diameter)
- MIN CREEP PATH OVER CONVOLUTIONS = 35.

Part Number: 171A108

(Please quote 10 digit code as below)

T0800	TB	45	E
Fixed type Code	Fixed Outline Code	Voltage Grade V _{CES} /100 45	Fixed format code

Typical order code: T0800TB45E ($V_{CES} = 4500V$)

WESTCODE

IXYS Corporation
1590 Buckeye Drive
Milpitas CA 95035-7418
Tel: +1 (408) 457 9000
Fax: +1 (408) 496 0670
E-mail: sales@ixys.net

~~www.westcode.com~~

www.ixys.net

IXYS Long Beach
IXYS Long Beach, Inc.
2500 Mira Mar Ave, Long Beach
CA 90815
Tel: +1 (562) 296 6584
Fax: +1 (562) 296 6585
E-mail: service@ixyslongbeach.com

The information contained herein is confidential and is protected by Copyright. The information may not be used or disclosed except with the written permission of and in the manner permitted by the proprietors Westcode Semiconductors Ltd.

© Westcode Semiconductors Ltd.

In the interest of product improvement, Westcode reserves the right to change specifications at any time without prior notice.

Devices with a suffix code (2-letter or letter/digit/letter combination) added to their generic code are not necessarily subject to the conditions and limits contained in this report.



Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.