

LSIC2SD120C10




Description

This series of silicon carbide (SiC) Schottky diodes has negligible reverse recovery current, high surge capability, and a maximum operating junction temperature of 175 °C. These diodes series are ideal for applications where improvements in efficiency, reliability, and thermal management are desired.

Features

- Positive temperature coefficient for safe operation and ease of paralleling
- 175 °C maximum operating junction temperature
- Excellent surge capability
- Extremely fast, temperature-independent switching behavior
- Dramatically reduced switching losses compared to Si bipolar diodes

Circuit Diagram TO-252-2L (DPAK)



Applications

- Boost diodes in PFC or DC/DC stages
- Switch-mode power supplies
- Uninterruptible power supplies
- Solar inverters
- Industrial motor drives
- EV charging stations

Environmental

- Littelfuse "RoHS" logo = RoHS conform
- Littelfuse "HF" logo = **HF** Halogen Free
- Littelfuse "PB-free" logo = PB-free lead plating

Maximum Ratings

Characteristics	Symbol	Conditions	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	-	1200	V
DC Blocking Voltage	V_R	$T_J = 25\text{ °C}$	1200	V
Continuous Forward Current	I_F	$T_C = 25\text{ °C}$	33	A
		$T_C = 135\text{ °C}$	16	
		$T_C = 156\text{ °C}$	10	
Non-Repetitive Forward Surge Current	I_{FSM}	$T_C = 25\text{ °C}, T_P = 10\text{ ms, Half sine pulse}$	80	A
Power Dissipation	P_{Tot}	$T_C = 25\text{ °C}$	176	W
		$T_C = 110\text{ °C}$	76	
Operating Junction Temperature	T_J	-	-55 to 175	°C
Storage Temperature	T_{STG}	-	-55 to 150	°C
Soldering Temperature	T_{sold}	-	260	°C

Electrical Characteristics

Characteristics	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Forward Voltage	V_F	$I_F = 10 \text{ A}, T_J = 25^\circ\text{C}$	-	1.5	1.8	V
		$I_F = 10 \text{ A}, T_J = 175^\circ\text{C}$	-	2.2		
Reverse Current	I_R	$V_R = 1200 \text{ V}, T_J = 25^\circ\text{C}$	-	<1	100	μA
		$V_R = 1200 \text{ V}, T_J = 175^\circ\text{C}$	-	10		
Total Capacitance	C	$V_R = 1 \text{ V}, f = 1 \text{ MHz}$	-	582		pF
		$V_R = 400 \text{ V}, f = 1 \text{ MHz}$	-	53		
		$V_R = 800 \text{ V}, f = 1 \text{ MHz}$	-	40		
Total Capacitive Charge	Q_C	$V_R = 800 \text{ V}, Q_C = \int_0^{V_R} C(V) dV$	-	57		nC

Footnote: $T_J = +25^\circ\text{C}$ unless otherwise specified

Thermal Characteristics

Characteristics	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Thermal Resistance	$R_{\theta JC}$	-	-	0.85		$^\circ\text{C}/\text{W}$

Figure 1: Typical Forward Characteristics




Figure 2: Typical Reverse Characteristics




Figure 3: Power Derating




Figure 4: Current Derating




Figure 5: Capacitance vs. Reverse Voltage




Figure 6: Capacitive Charge vs. Reverse Voltage




Figure 7: Stored Energy vs. Reverse Voltage






Figure 8: Transient Thermal Impedance



Part Numbering and Marking System




SIC = SiC Diode
 2 = Gen2
 SD = Schottky Diode
 120 = Voltage Rating (1200 V)
 C = TO-252-2L (DPAK)
 10 = Current Rating (10 A)
 YY = Year
 WW = Week
 D = Special code (fixed)
 ZZZZZZ-ZZ = Lot Number


Packing Options

Part Number	Marking	Packing Mode	M.O.Q
LSIC2SD120C10	SIC2SD120C10	Tape and Reel	2500

Dimensions TO-252-2L (DPAK)




Recommended Solder Pattern Layout



Symbol	Inches			Millimeters		
	Min	Nom	Max	Min	Nom	Max
A	0.085	0.090	0.095	2.16	2.29	2.41
A1	0	0.003	0.005	0	0.08	0.13
b	0.025	0.030	0.035	0.64	0.76	0.89
b3	0.195	0.200	0.215	4.95	5.08	5.46
c	0.018	0.020	0.024	0.46	0.51	0.61
C2	0.018	0.032	0.035	0.46	0.81	0.89
D	0.235	0.240	0.245	5.97	6.10	6.22
D1	0.205	-	-	5.21	-	-
E	0.250	0.260	0.265	6.35	6.60	6.73
E1	0.170	-	-	4.32	-	-
e	0.090 BSC			2.29 BSC		
H	0.370	0.387	0.410	9.40	9.83	10.41
L	0.040	0.045	0.050	1.02	1.14	1.27
L2	0.010 BSC			0.25 BSC		
L3	0.035	-	0.050	0.89	-	1.27
L4	0	-	0.006	0	-	0.15
P	0°	-	8°	0°	-	8°

Carrier Tape & Reel Specification TO-252-2L (DPAK)



1. Material: Black Conductive Polyester
2. 10 sprocket hole pitch cumulative tolerance ± 0.20
3. Camber not to exceed 1 mm in 100 mm.
4. Pocket position relative to sprocket hole measured as true position of pocket, not pocket hole.
5. Device orientation: TRL (leads perpendicular to the sprocket)
6. General tolerance is ± 0.10 mm unless otherwise specified.

COVER TAPE SPECS:

Width	: 13.5 mm
Base Material	: less than 1.2×10^{-9} ohms/square Transparent polyester, static dissipative
Adhesive Layer	: Polyethylene
Total Thickness	: 60 Micron
Tensile Strength	: 4-6 kg/mm ²
Elongation	: 91%
Tearing Strength	: 11 kg/mm ²
Shelf life	: 2 years

Technical drawing of a 5-hole punched tape reel. The drawing includes three views: a front view (left), a side view (top center), and a detail view of the central hub (bottom right).

- Front View (Left):** Shows a circular reel with five spokes. Dimensions include a spoke width of $2.5^{+0.5}$, a central hole diameter of $\phi 10.0^{+0.45}$, and a total diameter of $\phi 33.0$. Callouts 91, 16, 16, 71, and 6 are present.
- Side View (Top Center):** Shows the profile of the reel with a maximum width of 24.0 MAX. and a central hole diameter of $\phi 10.0^{+0.45}$. Callouts 11, 16, and 4 are present.
- Detail View (Bottom Right):** Shows the central hub with dimensions $X, 1.1$, 21 ± 0.8 , 13 ± 0.2 , and 2 ± 0.5 . Callouts 41, 16, 16, 51, 61, and X are present.

NOTES

- 1) WINDOW CLEARANCE ON BOTH SIDE DISK.
- 2) SURFACE RESISTANCE $\geq 10^7$ OHM AND $< 1 \times 10^{11}$ OHM. REFER TO IEC 6140-5-1.
- 3) RECYCLE LOGO WITH MATERIAL CODE "6" IN CIRCLE, ONE OR BOTH SIDE DISK.
- 4) DATE CODE IN CIRCLE ON ONE SIDE OF DISK.
- 5) TAPE WIDTH "16 mm" IN CIRCLE, TEXT HEIGHT 6 mm, ON BOTH SIDE DISK.
- 6) HUB SIZE INDICATION ON BOTH SIDE DISK.
- 7) AREA OF LABEL MIN 110 x 55.
- 8) NUMBER OF GROOVES ACCORDING TO PRODUCER, EITHER 3 OR 6.
- 9) DEPRESSION LINEAR SCALE IS PREFERRED, 10 mm INTERVAL, HEIGHT OF LETTERING 3 mm.

NON CRITICAL DIMENSIONS ACCORDING TO PRODUCER.

A-A
Scale: 5:1

0.4 $\pm$ 0.1

2.8 $\pm$ 0.3

© 2017 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: 10/02/17