



UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

●	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE
ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.

NO	COMPONENT NO	DESCRIPTION	MATERIAL			QTY/M	U/M	
			MATL SPEC	FINISH	DATE			
<b>BILL OF MATERIAL</b>								
			DRW	JCU	DATE	10/14/2009	SCALE	---
			CHK		DATE		SUPER DRW	
			APPD		DATE		RAW STK WT	
			TOLERANCE UNLESS OTHERWISE SPECIFIED			LBS/M		
			TWO PLACE DEC ±.01			FRACTION ±		
			THREE PLACE DEC ±.005			ANGULAR ±1°		
			<b>TITLE</b>					
			2P 280 MICRO RELAY +					
			2P MINI FUSE MODULE					
			<b>Littelfuse</b> DES PLAINES, ILLINOIS 60016					
			REVISION	DRWG. NO.	FINAL			
			A	03540551Z				
COPIES TO								
1 9 18								
2 10 19								
3 12 20								
4 13 21								
5 14 23								
6 15 33								
7 16 43								
8 17 53								
LTR	REVISION			CHK	APD			
A	000810ER - RELEASED							