



| REVISION |         |                         |
|----------|---------|-------------------------|
| REV      | DATE    | DESCRIPTION             |
| A        | 6/24/21 | 523870GCP - RELEASE MRY |

APPROXIMATE SHIPPING WEIGHT: 10 FUSES = 1.31 LB

|     |  |
|-----|--|
| <S> | CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE   |
| ●   | DENOTES CRITICAL CHARACTERISTICS.  |
| CPK | DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE   |
| Ⓢ   | DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS. |
| CP  | DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.               |

**A**

|              |                   |              |                               |
|--------------|-------------------|--------------|-------------------------------|
| MATL SPEC    |                   | FINISH       |                               |
| DRW<br>myork | DATE<br>6/14/2021 | SCALE<br>NTS | FINISH GOOD WT<br>GRAMS/PIECE |

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN BRACKETS [ ] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994

|                      |  |
|----------------------|--|
| 3RD ANGLE PROJECTION |  |
|----------------------|--|

**TITLE** FLNR-ID 35-60A OUTLINE

|                             |          |              |              |
|-----------------------------|----------|--------------|--------------|
| <br>CHICAGO, ILLINOIS 60631 | REVISION | DRWG NO.     | SHEET 1 OF 1 |
|                             | A        | OL-FLNR060ID |              |