

REVISION						
ATE	DESCRIPTION					
21/20	522213GCP - RELEASE MRY					
20/20	522414ECP/D - ADD DIMENSIONS MRY					

>	CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE							
)	DENOTES CRITICAL CHARACTERISTICS.							
K	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE							
5	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.							
5	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.							
EC			l					
		DATE	SCALE		FINISH GOOD WT			
11/11/2019			NIS	NTS GRAMS/PIECE				
ESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN TS [] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994								
DISCONNECT SWITCH 250A 1000VDC 2 POLE OUTLINE								
Littelfuse			REVISION	DRWG NO.	SHEET 1 OF 1			
CHICAGO, ILLINOIS 60631			В	OL-LS602502ES00L				